



Xyron® Pro 1255™

Product Specifications

Footprint	10.5" x 13" x 15" (26.7cm x 33cm x 38.1cm)
Weight/Packed Weight	14.75lbs (6.6kg) / 18.25lbs (8.2kg)
Document Thickness (max.)	0.125" (3.2mm)
Finished Document Width (max.)	11.75" (29.8cm)
Power Requirements	None
Cutter	Removable, replaceable cutter

Product Supply Description

The Xyron Pro 1255 is your complete professional document finishing system. Instantly applies laminate, adhesive or both. Perfect for presentations, comps, packaging mock-ups, signs, displays, and short-run labels.

- **Permanent High-Tack Adhesive:** Extremely aggressive adhesive instantly creates a permanent bond on most surfaces. Sets instantly and will not peel. Acid-Free.
- **Permanent Standard Adhesive:** Moderately aggressive adhesive creates a permanent bond on most surfaces. Can be touched to surface, peeled back quickly, and replaced. Acid-Free.
- **Repositionable Adhesive:** Allows items to be repositioned over and over. Easy removal from glass, walls, paper, and most other surfaces. Acid-Free.
- **Standard Use Laminate:** High gloss film suitable for use on a variety of substrates. Superior adhesion. Compatible with most media. Acid-Free.
- **Matte Laminate:** A high end clear laminate with minimal reflection. Acid-Free.
- **Combination—Laminate/Adhesive:** One of the laminate products described on the top surface and one of the Acid-Free adhesives described on the bottom surface. Acid-Free.

Part Number	Product Description	Material Length	Material Width	Laminate & Adhesive Combination Thickness (per side)	Mounting Adhesive Thickness	Adhesive pH	Mounting Adhesive Strength (1:10; 10-high)	PAT Approved
Adhesive Application Cartridges								
AT1251-100	Permanent High-Tack	100' (30.5m)	12" (30.5cm)	N/A	0.6mil (15.2mic)	Acid-Free	10	Yes
AT1255-100	Permanent Standard	100' (30.5m)	12" (30.5cm)	N/A	0.6mil (15.2mic)	Acid-Free	8	Yes
AT1256-100	Repositionable	100' (30.5m)	12" (30.5cm)	N/A	1.1mil (27.9mic)	Acid-Free	3	Yes
Laminate Cartridges								
DL1251-150	2-Sided Standard Use Laminate	150' (95.7m)	12" (30.5cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
Combination One Side Lamination / One Side Adhesive Application								
LAT1251-100	1 Side Standard Use Laminate 1 Side High-Tack Adhesive	100' (30.5m)	12" (30.5cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes
LAT1256-100	1 Side Standard Use Laminate 1 Side Repositionable Adhesive	100' (30.5m)	12" (30.5cm)	2.7mil (67.5mic)	1.1mil (27.9mic)	Acid-Free	3	Yes
MLAT1251-100	1 Side Matte Laminate 1 Side High-Tack Adhesive	100' (95.7m)	12" (30.5cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes
Cutter								
2342	Replaceable Cutter Bar and Blade Assembly							
2343	Replacement Tray							

Xyron

**Cold Laminators,
Refill Cartridges &
Roll Sets**

Most product in stock
& shipped same day

BRIGHT WHITE PAPER CO.

To Order Call **800-321-5716**
Fax 772-223-4040
International 772-223-5511
P.O. Box 2472
Palm City, FL 34991

www.xyronpro.com | 1.800.793.3523

An **Esselte** Company